

# Aire acondicionado Mono-Split 1x1 Mural Climate 5000 R32



Unidad interior



Unidad exterior



Modelo	Referencia	Código EAN	Capacidad (kW) Nominal (min-max)	
			Frío	Calor
<b>Mono Split Mural Climate RAC 5000 2,6-2 R32</b>	<b>7731200359</b>	<b>4062321104573</b>	<b>2,6</b> (0,9-3,4)	<b>2,9</b> (0,8-3,4)
Climate RAC 5000 2,6-3 IBW	7733700722	4062321087890	-	-
Climate RAC 5000 2,6-2 OUE	8733500822	4057749948922	-	-
<b>Mono Split Mural Climate RAC 5000 3,5-2 R32</b>	<b>7731200360</b>	<b>4062321104580</b>	<b>3,5</b> (1,1-4,2)	<b>3,8</b> (1,1-4,2)
Climate RAC 5000 5,3-3 IBW	7733700723	4062321087906	-	-
Climate RAC 5000 3,5-2 OUE	8733500823	4057749948939	-	-
<b>Mono Split Mural Climate RAC 5000 5,3-2 R32</b>	<b>7731200361</b>	<b>4062321104597</b>	<b>5,3</b> (1,8-6,1)	<b>5,6</b> (1,4-6,7)
Climate RAC 5000 5,3-3 IBW	7733700724	4062321087913	-	-
Climate RAC 5000 5,3-2 OUE	8733500824	4057749948946	-	-
<b>Mono Split Mural Climate RAC 5000 7,0-2 R32</b>	<b>7731200362</b>	<b>4062321104603</b>	<b>7,0</b> (2,7-7,9)	<b>7,3</b> (1,6-8,8)
Climate RAC 5000 7-3 IBW	7733700725	4062321087920	-	-
Climate RAC 5000 7-2 OUE	8733500825	4057749948953	-	-

Datos técnicos		Unidades	Climate RAC 5000 2,6-2 R32	Climate RAC 5000 3,5-2 R32	Climate RAC 5000 5,3-2 R32	Climate RAC 5000 7,0-2 R32
Capacidad Frío		kW/h	<b>2,6</b> (0,9 - 3,4)	<b>3,5</b> (1,1 - 4,2)	<b>5,3</b> (1,8 - 6,1)	<b>7,0</b> (2,7 - 7,9)
		Kcal/h	2268 (756-2923)	3024 (958-3578)	4536 (1562-5267)	6048 (1789-6834)
Capacidad Calor		kW/h	<b>2,9</b> (0,8 - 3,4)	<b>3,8</b> (1,1 - 4,2)	<b>5,6</b> (1,4 - 6,7)	<b>7,3</b> (1,6 - 8,8)
		Kcal/h	2579 (688-3095)	3439 (757-3783)	4987 (963-5847)	6048 (2175-6535)
Consumo Frío		W	710 (100 - 1240)	1237 (130 - 1580)	1539 (140 - 2360)	2345 (160 - 2960)
Consumo Calor		W	739 (120 - 1200)	964 (100 - 1580)	1480 (200 - 2410)	2035 (260 - 3140)
Frío estacional	SEER (Etiqueta)	W/W	6,2 (A <sup>+</sup> )	6,1 (A <sup>+</sup> )	7,1 (A <sup>+</sup> )	6,1 (A <sup>+</sup> )
Calor (clima cálido /medio)	SCOP (Etiqueta)	W/W	4,9 (A <sup>+</sup> )/4,0 (A <sup>-</sup> )	4,6 (A <sup>+</sup> )/4,0 (A <sup>-</sup> )	5,2 (A <sup>+</sup> )/4,0 (A <sup>-</sup> )	5,0 (A <sup>+</sup> )/4,0 (A <sup>-</sup> )
Espectro ErP			A <sup>+</sup> →D	A <sup>+</sup> →D	A <sup>+</sup> →D	A <sup>+</sup> →D
Alimentación		V-Hz	220-240V-50Hz	220-240V-50Hz	220-240V-50Hz	220-240V-50Hz
<b>Unidades interiores</b>			<b>Climate RAC 5000 2,6-3 IBW</b>	<b>Climate RAC 5000 3,5-3 IBW</b>	<b>Climate RAC 5000 5,3-3 IBW</b>	<b>Climate RAC 5000 7-3 IBW</b>
Nivel de presión sonora (Si/Bajo/Medio/Alto)		dB(A)	21/26/30/40	22/26/34/40	25/30/37/44	28/35/42/45
Dimensiones (Ancho x Profundo x Alto)		mm	805x194x285	805x194x285	957x213x302	1040x220x327
Peso Neto/Bruto		Kg	7,6/9,7	7,6/9,7	10,0/13,0	12,3/15,8
<b>Unidades exteriores</b>			<b>Climate RAC 5000 2,6-2 OUE</b>	<b>Climate RAC 5000 3,5-2 OUE</b>	<b>Climate RAC 5000 5,3-2 OUE</b>	<b>Climate RAC 5000 7-2 OUE</b>
Caudal de aire		m <sup>3</sup> /h	1700	1700	2500	3000
Nivel de presión sonora		dB(A)	56	56	56	60
Dimensiones (Ancho x Profundo x Alto)		mm	700x275x550	700x275x550	800x333x554	845x363x702
Peso Neto/Bruto		Kg	22,8/25,2	22,7/25,2	34,0/36,7	51,5/54,5
Refrigerante	Tipo		R32	R32	R32	R32
	GWP		675	675	675	675
	Cantidad carga	Kg	0,5	0,5	1,0	1,6
	Equivalente de CO <sub>2</sub>	Ton	0,338	0,338	0,675	1,080
	Distancia estándar	m	5	5	5	5
	Carga adicional	g/m	12	12	12	24
Tubería refrigerante	Líquido / Gas	pulg.	1/4"-3/8"	1/4"-3/8"	1/4"-1/2"	3/8"-5/8"
	Máx. Longitud	m	25	25	30	50
	Máx. Vertical	m	10	10	20	25

(1) Precio base de venta. IVA no incluido.  
Contiene gas refrigerante R32 con GWP = 675.