

TCL AC | Smart Air, Soft Care

MONO SPLIT LIGHT COMMERCIAL AIR CONDITIONER

Super Slim Air duct D Series

M18D1W2




Ultra-thin Design

Ultra-thin body for concealed installation and can match a variety of decoration styles.



Fresh Air Intake

To make indoor air healthier and more comfortable.



Drain Pump

For convenient to installation and improving drainage efficiency.



Wide Range of Static Pressure

Providing comfortable flow to multiple area.



Flexible Installation


You can choose back air intake or down air intake.



Dual Drainage

You can choose to drain from the left or right.


Hotel Mode



Door Card, Window Switch, Fire Alarm

When a guest exits the room and removes the door card, when a window is left open, in the event of a fire alarm :

The air conditioner is programmed to automatically power down.



Wire Controller

Guests can easily adjust the temperature and settings according to their preference.



Compliant To BMS System & Airzone

Compliant to building management system and Airzone for more convenient monitoring and control

TCL AC | Smart Air, Soft Care

MONO SPLIT LIGHT COMMERCIAL AIR CONDITIONER

Super Slim Air duct D Series

M18D1W2

Functions



Ultra-Thin Design



Fresh Air Intake



Built-In Drain Pump



Flexible Installation



Dual Drainage



Hotel Mode



Wired Control/
Remote Control



IOT Wifi Control



Inverter Technology



Heating & Cooling



Cooling Under
Extreme Condition




Heating Under
Extreme Condition



Cooling



Heating



Technical Specifications

			Air Duct
Model Name			M18D1W2
Ean Code			8720568107271
Indoor unit model name			MN18DW2
Ean code			8720568107400
Outdoor unit model name			MT1813
Ean code			8720568107431
Main Specifications			
Cooling	Declared cooling capacity (mini-maxi)	Btu/h	16050(2115-17400)
	Declared cooling capacity (mini-maxi)	W	4700(620-5100)
	Pdesignnc	W	5000
	Indoor cooling operating current	A	0,21
	Indoor cooling power consumption (mini-maxi)	W	48
	Outdoor cooling operating current (mini-maxi)	A	6.8(1.6-12.0)
Heating	Outdoor cooling Power consumption (mini-maxi)	W	1480(200-2150)
	Declared heating capacity (mini-maxi)	Btu/h	16050(2590-18150)
	Declared heating capacity (mini-maxi)	W	4700(760-5320)
	Pdesignnh average	W	3900
	Indoor heating operating current	A	0,21
	Indoor heating power consumption	W	48
	Outdoor heating operating current (mini-maxi)	A	6.0(1.7-12.0)
	Outdoor heating power consumption (mini-maxi)	W	1390(230-2150)
Performance			
Cooling	EER declared		3,20
	SEER declared		6,1
Heating	COP average declared		3,20
	SCOP declared		4
Moisture removal		L/h	2
Indoor sound power (s/h/m/l/mute)		dB (A)	56/53/50/48/46/42/38
Outdoor sound power		dB (A)	65
Indoor sound pressure (s/h/m/l/mute)		dB (A)	46/43/40/38/36/32/28
Outdoor sound pressure		dB (A)	55
Energy Class			
Cooling			A++
Heating			A+
Outdoor Operating Temperature Range			
Cooling mode		°C	15 / 53°C
Heating mode		°C	-20 / 30°
Logistic Data			
Indoor Unit	Product size (w x h x d)	mm	920×200×490
	Product weight	kg	18
	Packaging size (w x h x d)	mm	1120×250×555
	Packaging weight	kg	21
Outdoor Unit	Product size (w x h x d)	mm	853×602×349
	Product weight	kg	30
	Packaging size (w x h x d)	mm	890×628×385
	Packaging weight	kg	32,5
Electrical Connection			
Power supply Indoor Unit			220-240V~/50Hz/1P
Power supply Outdoor Unit			220-240V~/50Hz/1P
Connecting wiring (core x size)			4×0.75mm ²
Refrigeration Fluid And Connection			
Refrigerant type			R32
Charge			0.96kg
Gwp			675
Co2 equivalent			0.648tonnes
Max. refrigerant pipe length(m)		m	25
Max. difference in level		m	10
Gas connecting pipe		Inches	3/8"
Liquid connecting pipe (inches)		Inches	1/4"

*Warranty may vary by country / Specifications are subject to change without notice / Photos are not contractual.