

SaveIN

Category	Wall Mount	Wall Mount	Wall Mount
Product Picture			
Type	HEAT PUMP	HEAT PUMP	HEAT PUMP
Control type	Remote Controller	Remote Controller	Remote Controller
Cooling capacity(Btu/h)	9000	12000	18000
Heating capacity(Btu/h)	9000	12000	18000
Declared cooling capacity (W)	2620(940~3300)	3400(1000~3770)	5140(1250~5910)
Declared heating capacity (W)	2700(1000~3810)	3420(1000~3810)	5210(1250~6070)
Indoor sound power(S/H/M/L/Mute) (dB(A))	53/49/43/35/32	53/49/43/35/32	56/53/47/41/37
Indoor sound pressure(S/H/M/L/Mute)(dB(A))	42/38/32/26/22	42/38/32/26/22	47/43/37/31/27
Electrical Data			
Power supply	220-240V~/50HZ	220-240V~/50HZ	220-240V~/50HZ
Voltage Range(V)	165~265	165~265	165~265
Cooling Current(A)	0,2	0,2	0,2
Heating Current (A)	0,2	0,2	0,2
Cooling Power Input (W)	35	35	35
Heating Power Input (W)	35	35	35
Fan System			
Indoor air circulation (m³/h)	550/570	550/570	800/800
Indoor fan type	DC	DC	DC
Connections			
Connecting Wiring (Core x Size)	4×0.75mm²	4×0.75mm²	4×0.75mm²
Power Cord Wiring (Core x Size)	/	/	/
Refrigerant coupling	Flare	Flare	Flare
Liquid Connecting Pipe (inches)	1/4"	1/4"	1/4"
Gas Connecting Pipe (inches)	3/8"	3/8"	3/8"
Others			
Indoor Net dimensions (W x H x D) (mm)	778×272×192	778×272×192	910×305×195
Indoor Net weight (kg)	7,3	7,3	9
Indoor Packing dimensions (W x H x D) (mm)	840×335×255	840×335×255	979×380×265
Indoor Gross weight (kg)	9,5	9,5	11
static pressure	/	/	/
Panel Net dimensions (W x H x D)	/	/	/
Panel Net weight (kg)	/	/	/
Panel Packing dimensions(W x H x D)	/	/	/
Panel Gross weight (kg)	/	/	/
Loading Capacity w/o pipe (40 HQ)	880	880	660
Indoor Stacking Limit (unit)			