

Termos eléctricos

	Modelo	Referencia	Código EAN	Capacidad (litros)	Potencia (kW)	Medidas alto x Ø (mm.)	Precio base de venta €	Coste de reciclado repercutido (*)
	Gama Elacell							
	HS 35-3B	7 731 407 060	4 010 009 103 653	35	1,4	624 x 391 Ø	194	1,72
	HS 50-3B	7 731 408 059	4 010 009 103 707	50	1,6	682 x 452 Ø	224	1,72
	HS 80-3B	7 731 412 010	4 010 009 103 790	80	2	948 x 452 Ø	286	3,45
	HS 100-3B	7 731 416 059	4 010 009 103 875	100	2	1.128 x 452 Ø	316	3,45
	Gama Elacell Smart							
	ES 15-1M	7 736 500 082	4 047 416 747 842	15	1,2	414 x 320 x 317	115	1,72
	ES 30-1M	7 736 500 083	4 047 416 747 859	30	1,5	586 x 353 Ø	160	1,72
	ES 50-1M	7 736 500 084	4 047 416 747 866	50	1,5	553 x 450 Ø	179	1,72
	ES 75-1M	7 736 500 085	4 047 416 747 880	75	2	758 x 450 Ø	206	3,45
	ES 100-1M	7 736 500 086	4 047 416 747 897	100	2	913 x 450 Ø	230	3,45
	ES 150-1M	7 736 501 544	4 051 516 805 227	150	2,2	1.185 x 505 Ø	435	3,45
	ES 200-1M	7 736 501 546	4 051 516 805 241	200	2,5	1.505 x 505 Ø	500	3,45
	Gama HS...							
	HS 300	7 709 500 289	4 047 416 938 790	300	3	1.820 x 625 Ø	760	3,45
	HS 500	7 709 500 302	4 047 416 143 217	500	6	1.870 x 714 Ø	2.127	3,45

Todos los modelos HS... y Elacell están equipados con luz LED de funcionamiento.
 Todos los modelos de la gama Elacell HS...3B tienen resistencias envainadas e instalación vertical y horizontal.

Calentadores eléctricos instantáneos

	Modelo	Referencia	Código EAN	Caudal (l/min.)	Potencia (kW)	alto ancho fondo (mm.)	Precio base de venta €	Coste de reciclado repercutido (*) Precio unitario € (*) DTU/RD 208 / 2005
	ED 6	7 733 000 016	4 047 416 571 737	3,4	6	235 x 141 x 100	320	1,72
	ED 18-2S	7 733 004 019	4 010 009 704 157	9,8	18		380	1,72
	ED 21-2S	7 733 006 019	4 010 009 704 171	11,5	21	472 x 236 x 139	390	1,72
	ED 24-2S	7 733 008 015	4 010 009 704 195	13,1	24		410	1,72

Tensión voltios C. Trifásica 380 Δ El modelo ED 6 es monofásico a 220 - 240 V

Acumuladores de agua a gas

	Modelo	Referencia	Código EAN	Capacidad (litros)	Tipo gas	Medidas alto (mm.) x Ø	Precio base de venta €
	S 120 KP	7 708 402 011	4 010 009 016 304	115	B/N	1.277 x 500 Ø	730
	S 160 KP	7 708 403 011	4 010 009 016 342	155	B/N	1.477 x 500 Ø	820
	S 190 KP	7 708 404 012	4 010 009 016 373	190	B/N	1.727 x 500 Ø	1.000
	S 290 KP	7 708 405 008	4 010 009 016 397	280	B/N	1.681 x 635 Ø	2.060
	VÁLVULA DE SEGURIDAD (6,0 bar.)	7 719 000 779	4 010 009 050 933		Obligatoria instalación		17

Equipado con dispositivo de control de gases.